



CGPDTM Patent Examiner

Previous Year Paper (Mains) (Polymer Sc) Oct, 2015



ALL EXAMS, ONE SUBSCRIPTION



1,00,000+ Mock Tests



Personalised Report Card



Unlimited Re-Attempt



600+ Exam Covered



25,000+ Previous Year Papers



500% Refund

















ATTEMPT FREE MOCK NOW







102

Polymer Science

TIME: 3 HOURS

MAXIMUM MARKS: 300

INSTRUCTIONS:

- 1. All questions are compulsory.
- **2.** Question Paper may be divided into **4 (four)** Sections from **Section-A** to **Section-D** and carry marks as under :
 - **a.** Section A Total 3 Questions having two parts, i.e. (a) and (b) each questions carries 12 marks \times 3 Questions = Total 36 Marks.
 - **b.** Section B Total 3 Questions having two parts, i.e. (a) and (b) each questions carries 20 marks × 3 Questions = Total 60 Marks.
 - c. Section C Total 3 Questions having two parts, i.e. (a) and (b) each questions carries 28 marks × 3 Questions = Total 84 Marks.
 - d. Section D Total 3 Questions having two parts, i.e. (a) and (b) each questions carries 40 marks \times 3 Questions = Total 120 Marks.

SECTION - A

(Each question is of 12 marks and each sub part (a) and (b) are of 6 marks each)

- 1 (a) Write the structure of the monomers used for the synthesis of nylon-46, poly (ethylene terephthallate) and nitrile rubber.
 - (b) When two monomers react to form a copolymer, state the conditions under which they form a random, alternating and block copolymer.
- 2 (a) Write the role of each of the following additives in rubber technology:
 - (i) Pentachlorothiophenol
 - (ii) Mercaptobenzothiazole
 - (iii) Paraffin wax





- (b) Identify the process by which the following plastic products are manufactured:
 - (iv) disposable cups
 - (v) water bottle
 - (vi) chair
- 3 (a) How are poly organophosphazenes synthesized?
 - (b) What is EPDM rubber? Give structures of the common dienes that are used in the synthesis of EPDM rubbers.

SECTION - B

(Each question is of 20 marks and each sub part (a) and (b) are of 10 marks each)

- 4 (a) What are the various thermodynamic factors influencing the miscibility of two polymers? Why does polyethylene and polypropylene form an immiscible blend?
 - (b) How much of a low molecular weight plasticizer with $T_g = -80^{\circ}\text{C}$ should be added to a film of nylon 66 inorder to reduce the T_g from 50°C to 25°C.
- 5 Write short notes on:
 - (a) Reaction Injection Molding
 - (b) Thermoforming
- 6 (a) What is glass transition temperature? What are the various methods used to determine glass transition temperature?
 - (b) Explain why T_g of polyethylene is less than that of polypropylene which is less than that of polystyrene.





SECTION - C

(Each question is of 28 marks and each sub part (a) and (b) are of 14 marks each)

- 7 Explain the following:
 - (a) Biaxially oriented polypropylene films are transparent.
 - (b) HIPS has a higher toughness than polystyrene.
- 8 Give formulation for the following specifying the approximate range of each ingredient:
 - (a) PVC based general purpose insulation compound
 - (b) Truck tire thread
- 9 (a) State the essential requirements to be fulfilled so that the molecualr weight of a particular polymer can be estimated by end group analysis.
 - (b) 2.7 g of a linear polyester containing acid groups at both ends requires 15 mL of 0.1N potassium hydroxide for complete neutralization. Calculate \overline{M}_{p} of the polyester?

SECTION - D

(Each question is of 40 marks and each sub part (a) and (b) are of 20 marks each)

- 10 (a) 5g of a monodisperse polystyrene sample of molecular weight 10,000 gmol⁻¹ was mixed with 10g of a monodisperse polystyrene sample of molecular weight 20,000 gmol⁻¹. Calculate the polydispersity index of the mixture?
 - (b) Show that in an Ubbelohde viscometer, the relative viscosity is equal to the ratio of the time of flow of the polymer solution to that of a solvent between two appropriate marks.

102] 3 [Contd...





- 11 (a) In a unidirectional carbon fibre/epoxy composite, the modular ratio is 40 and fibres take up 50% of the cross-section. Calcualte the percentage of applied force taken by the fibres.
 - (b) Calculate the maximum and average fibre stresses for glass fibres which have a diameter of $5 \, \mu m$ and a length of 2.5 mm. The interfacial shear strength is $4 \, \text{MN/m}^2$ and $l_t / l = 0.3$ (l_t is the load transfer length and l is the fibre length).
- 12 (a) Explain the significance of the following in polymer science:
 - (i) polydispersity
 - (ii) solubility parameter
 - (iii) loss tangent in dynamic mechanical analysis
 - (iv) X-ray diffraction technique
 - (b) The density of crystalline polyethylene is 0.996 g cm⁻³ and the density of amorphous polyethylene is 0.866 g cm⁻³. Calculate the percentage crystallinity in a sample of linear polyethylene of density 0.970 g cm⁻³?

